

1/3 DWPI(C) Derwent- image

AN - 2000-425859 [37]

XA - C2000-129329

XP - N2000-317693

TI - Non-aqueous electrolyte battery, includes air-tight sealing board obtained by molding polymeric material to seal opening of battery container

DC - A85 L03 X16

PA - (SAOL ) SANYO ELECTRIC CO LTD

NP - 1

NC - 1

PN - JP2000138041 A 20000516 DW2000-37 H01M-002/08 10p \*

AP: 1998JP-0311359 19981030

PR - 1998JP-0311359 19981030

IC - H01M-002/08 H01M-002/02 H01M-002/12

AB - JP2000138041 A

NOVELTY - An electricity generating element is impregnated into the non-aqueous electrolyte battery container (101) and an opening is sealed with a board (103) obtained by molding polymeric material.

- USE - Non-aqueous electrolyte battery.

- ADVANTAGE - The capacitive maintenance property and stability of the non-aqueous electrolyte battery are raised.

- DESCRIPTION OF DRAWING(S) - The figure shows the non-aqueous electrolyte battery.


- Electrolyte battery container 10

- Sealing board 103(Dwg. 1/5)

MC - CPI: A11-B01 A12-E06C L03-E

- EPI: X16-A02 X16-B01F X16-F01A

UP - 2000-37



BEST AVAILABLE COPY